



23-400: Stainless Steel Liquid Level Gauge



Overview

Ideal for handling alcohol solvents, acetic acid and ketones. Automatic models conform to ASME requirements; aluminum and composition handwheels.

Features

- PTFE reinforced gauge glass gaskets, stem packings
- Chemical resistant PTFE seat
- 5/16" diameter full flow all SS drain valve with safety handle
- Guard rod bracket to accommodate four SS guard rods
- Rated 500 psig @ 450°F (NOTE: Service ratings are subject to pressure / temperature ratings of gauge glass and glass gaskets. Regular gauge glass is used in the standard water gauges unless otherwise noted as red line or high pressure.)

Dimensions

Part No.	Size	WT/100 lbs./kg	GLASS O D & LENGTH	Wheel Type	Water Gauges
23-401-00	1/2 15	385.000 174.633	5/8" x 12" 16 x 300	Aluminum	Non-Automatic
23-402-00	1/2 15	385.000 174.633	5/8" x 12" 16 x 300	Composition	Non-Automatic
23-404-00	3/4 20	450.000 204.117	3/4" x 16" 20 x 400	Aluminum	Non-Automatic
23-405-00	3/4 20	450.000 204.117	3/4" x 16" 20 x 400	Composition	Non-Automatic

Options

Suffix Number	Specification
-00	Standard Gauge w/Standard Glass & Rod
-01	Top only
-02	Bottom only
-03	Standard Gauge Less Glass and Rod
-10	For Special Gauges and Gauges With Non-Standard Glass and Rod Lengths